

Product Data Sheet



PDL-16-2/0-3

Listed Power Distribution Block
 175 Amps, 600 Volts (AC/DC)
 1,000V AC/DC CE (IEC 60947-7-1)



Wire Range:

Line side: (1) 2/0 - #14 AWG

Load Side: (6) #4 - #14 AWG

Electrical Ratings:

- 175A copper wire, 135A aluminum wire (Based on NEC Table 310-16, 75°C columns)
- CE Rated Voltage (U_i): 1,000 V AC/DC per IEC 60947-7-1
- Material Group: IIIa
- Pollution Degree: 3
- 600 Volts AC/DC (Service Equipment according to National Electrical Code, NFPA 70)
- Minimum enclosure size: 16 X 12 X 6
- Factory and Field Wiring

Short Circuit Current Ratings (Copper wire only):

Suitable Conductors (kcmil/AWG)		Overcurrent Protection Fuse Required Class/Max Amp Rating						SCCR, RMS SYM Amps	Volts Max
Line	Load	J	T	RK1	RK5	G	CC		
2/0 - 6	4 - 10	200	200	200	60	60	30	100,000	600

		Overcurrent Protection Circuit Breaker Required				SCCR, RMS SYM Amps	Volts Max
Line	Load	Mfr	Type		Max Amp		
2/0 - 2	4 - 8	Square D		JLL36250	250	65,000	480
2/0 - 6	4 - 12	Allen Bradley		14OU-H6	125	50,000	480
2/0 - 6	4 - 12	Allen Bradley		14OU-H0	125	50,000	480
2/0 - 4	4 - 8	Allen Bradley		14OU-J6	125	35,000	480
2/0 - 4	4 - 8	Allen Bradley		14OU-J0	125	35,000	480

Mechanical Ratings:

- Maximum insulator base temperature: 125°C (257°F) UL RTI
- Maximum insulator base plate temperature: 130°C (266°F) UL RTI
- Flammability rating of insulator base: UL 94 V-0


* Use outside these ratings needs to be judged in the end-use application.

Materials:

- Connector: High conductivity aluminum, tin plated
- Insulator base and covers: Glass filled polycarbonate (thermoplastic)
- Insulator base plate: Phenolic laminate
- Terminal set screws: Steel, nickel plated and Aluminum, zinc plated
- Mounting screws: Steel, zinc plated

Agency Approvals:

- UL Listed, File No. E112158
- Investigated to UL 1953
- UL 508A Feeder Circuit Terminal Spacing for up to 600 Volts
- CSA Certified, CSA C22.2 No. 158, File No MC 249467
- 600V Rating for Class 6228 01 – Use Groups A, B, C
- CE compliant to IEC 60947-7-1
- RoHS Compliant




Wire Approvals:

Line Side Wire Approvals:

Wire Size	Torque		Copper Wire Stranding Classes - Number of Strands		
	N.m	in. lbs	Solid	Class B	Class C
2/0 AWG	13.6	120		19	37
1/0	13.6	120		19	37
2	13.6	120		19	37
4	13.6	120		7	19
6	13.6	120		7	19
8	4.5	40		7	19
10	4.0	35	1	7	19
12	4.0	35	1	7	19
14	4.0	35	1	7	19

Aluminum stranded wire range: 2/0 – 14 AWG (70 – 2.5 mm²)



Load Side Wire Approvals:

Wire Size	Torque		Copper Wire Stranding Classes - Number of Strands		
	N.m	in. lbs	Solid	Class B	Class C
4	4.0	35		7	19
6	4.0	35		7	19
8	4.0	35		7	19
10	4.0	35	1	(1-2)* 7	(1-2)* 19
12	4.0	35	1	(1-4)* 7	(1-4)* 19
14	4.0	35	1	(1-4)* 7	(1-4)* 19

* Multiple conductor approvals for **LOAD** side only. (copper wire only)

Aluminum stranded wire range: #4 – #14 AWG

- Wire strip length, line side tap – 11/16”
- Wire strip length, load side tap, top row - 3/8, bottom row – 13/16”

- Panel mountable: #10 (5 mm) fastener, torque to 25-30 in. lbs.
- Hex keys needed: #4 tap – 1/8”, 2/0 tap – 5/16”

Accessories:

- Marker Strips. MS-1-S (three required)

