



**SKU:** CTL-2/0

**UPC:** 0783669128055

**Features & Benefits:**

**Description:** Surecrimp Copper Compression Sleeve, Conductor Size 2/0, Long Barrel, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-45
ILSCOs Die Index Number	I-45
Number of Conductors	1
Sight Window	No
Slotted	No

### Dimensions

Height (IN)	0.562
Height BX (IN)	2.25
Height (mm)	14.2748
Inside Diameter (IN)	0.437
Inside Diameter (mm)	11.0998
Length (IN)	3.125
Length (mm)	79.375
Outside Diameter (IN)	0.562
Outside Diameter (mm)	14.2748
Weight (LB)	0.128
Weight BX (LB)	2.187
Width (IN)	0.562
Width BX (IN)	5
Width (mm)	14.2748

### Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	2/0 Str - 4 Str
Flex Conductor Range	1/0 G,H,I,K,M,DLO



### Material and Finish

Conductor Material	Copper
Connector Finish Material	Tin
	Copper

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-1
UPC Code	78366912805

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207

### Environment and Temperature

Temperature Rating	90°C
--------------------	------

### Color

Color	Silver
Color Code	Black

### Voltage

Voltage Rating	35 kV
----------------	-------