



**SKU:** TA-350

**UPC:** 0783669889932

**Features & Benefits:**

**Description:** Aluminum Mechanical Lug, Conductor Range 350-6, 1 Port, 1 Hole, 3/8in Bolt Size, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

|                            |            |
|----------------------------|------------|
| Connection                 | Mechanical |
| Contains DE-OX®            | No         |
| Mounting Hole Type         | Thru       |
| Number of Conductors       | 1          |
| Number of Mounting Holes   | 1          |
| Number of Poles            | 1          |
| Number of Ports / Wireways | 1          |

### Dimensions

|                              |              |
|------------------------------|--------------|
| Dimension G (IN)             | 0.5          |
| Drive Size Main              | 3/8          |
| Drive Type Main              | Internal Hex |
| Height (IN)                  | 1.25         |
| Height BX (IN)               | 3.75         |
| Height (mm)                  | 31.75        |
| Length (IN)                  | 2.25         |
| Length (mm)                  | 57.15        |
| Mounting Bolt/Stud Size (mm) | 965.2        |
| Mounting Hole Diameter (IN)  | 0.406        |
| Mounting Hole Diameter (mm)  | 10.3124      |
| Mounting Hole Spacing (mm)   | 0            |
| Tang Length (IN)             | 1.125        |
| Tang Length (mm)             | 28.575       |
| Tang Thickness (IN)          | 0.25         |
| Tang Thickness (mm)          | 6.35         |
| Tang Width (IN)              | 1.125        |
| Tang Width (mm)              | 28.575       |
| Weight (LB)                  | 0.163        |
| Weight BX (LB)               | 4.285        |
| Width (IN)                   | 1.125        |
| Width BX (IN)                | 6            |
| Width (mm)                   | 28.575       |

### Material and Finish

|                    |        |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish   | Tin    |
| Insulation         | NA     |



|                                |          |
|--------------------------------|----------|
| Material                       | Aluminum |
| Wire Binding Hardware Finish   | Tin      |
| Wire Binding Hardware Material | Aluminum |

### Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### Bolt and Screw Sizes

|  |     |
|--|-----|
| Mounting Bolt/Stud Size                | 3/8 |
| Number of Wire Binding Screws per Port | 1   |
| Wire Binding Screw Size                | 3/4 |
| Wire Binding Torque                    | 375 |

### General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 1               |
| Carton Quantity Description | STD PACK QTY 25 |
| Direct Burial               | No              |
| Dual Rated                  | Yes             |
| NEMA Code                   | S-588-3         |
| UPC Code                    | 78366988993     |

### Testing Standards

|                          |   |
|--------------------------|---|
| CSA File Number          | LR-29601  |
| CSA Standard             | C22.2 No. 65-03   |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| ROHS Indicator           | IND   |
| UL Control Number        | 453G  |
| UL / CULUS Specification | UL 467 Listed   |
| UL File Number           | E6207   |

### Environment and Temperature

|                    |      |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

### Color

|       |        |
|-------|--------|
| Color | Silver |
|-------|--------|

### Conductor Ranges

|  |                   |
|--|-------------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA                |
| Conductor Range AL Stranded (Primary, run, main, line) | 350 kcmil - 6 Str |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA                |
| Conductor Range CU Solid (Primary, run, main, line)    | NA                |
| Conductor Range CU Solid (Secondary, tap, load)        | NA                |
| Conductor Range CU Stranded (Primary, run, main, line) | 350 kcmil - 6 Str |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA                |
| Conductor Range AL Solid (Primary, run, main, line)    | NA                |
| Wire Combinations                                      | NA                |

*Voltage*

**Voltage Rating**

35 kV